

# ENS202EXT

## LONG RANGE WIRELESS 11N OUTDOOR AP/CB

IEEE802.11b/g/n    2T+2R    300Mbps    High Performance



**ENS202EXT** Wireless Outdoor unit provides not only external antenna connectors for antenna upgrade, but also high output power and high sensitivity can extend the transmission range to deliver a stable wireless connection. ENS202EXT integrates 4 operation modes: Access Point, Client Bridge, Client Router and WDS.

Advanced multi-function operation modes offer flexibility in constructing scalable wireless networks for all possible applications. ENS202EXT is designed to deliver reliable service under harsh outdoor environment with certified IP65 protection and tailored to accommodate multimedia streaming services with data-rate up to 300Mbps. Most importantly, it is built-in encryption standards (WEP, WPA, WPA2, TKIP/AES and IEEE802.1x) ensure maximum security and compatibility.

### **Package Contents**

- 1 x ENS202EXT
- 2 x 2.4GHz 5dBi Omni Antenna
- 1 x Power Adapter (24V/0.6A)
- 1 x PoE Injector (EPE1212)
- 1 x Pole Mount set
- 1 x Screw Set
- 1 x CD(User Manual)
- 1 x Quick Guide
- 1 x Supporting Card

# ENS202EXT

## LONG RANGE WIRELESS 11N OUTDOOR AP/CB

IEEE802.11b/g/n    2T+2R    300Mbps    High Performance

### FEATURES

#### Hardware Features

<b>High output power</b>	<i>Transmit high output power programmable for different country selections</i>
<b>High Data Rate</b>	<i>High speed transmitting rate up to 300Mbps with 2T2R 802.11n</i>
<b>Long range transmitting</b>	<i>Transmit power control and distance control (ACK timeout)</i>
<b>Signal Strength Display</b>	<i>Indicate RF signal strength to be shown as LEDs of 3 colors, making network build-up easier. LED indicators have the best transmit and receive signal for traffic communication</i>
<b>PoE Support</b>	<i>Support proprietary 24V passive power over Ethernet</i>

#### Software Features

<b>Multiple SSID</b>	<i>4 SSID supported. Each SSID can set itself wireless or WAN access setting</i>
<b>PPPoE</b>	<i>Point-to-Point Protocol over Ethernet at Client Router mode. This function will keep trying when failed or disconnected</i>
<b>PPTP</b>	<i>Point-to-Point Tunneling Protocol (PPTP) is a method for implementing virtual private networks</i>
<b>VLAN Pass-through</b>	<i>Support VLAN Pass-through</i>
<b>Firmware Upgrade</b>	<i>Upgrading firmware via web browser, setting are reserved after upgrade</i>
<b>Reset &amp; Backup</b>	<i>Reset to factory default. User can export all setting into a file via WEB</i>
<b>Ping &amp; Trace Route</b>	<i>Built-in PING function &amp; Trace Route function in Web GUI</i>
<b>MIB</b>	<i>MIB I, MIB II(RFC1213), Private MIB</i>
<b>SNMP</b>	<i>V1, V2c, V3</i>

### SPECIFICATION

#### Hardware Specification

<b>Physical Interface</b>	2 x RJ-45 for 10/100 Fast Ethernet 1 x Reset Button
<b>Power Requirements</b>	- Active Ethernet (Power over Ethernet) - Proprietary PoE design

# ENS20EXT

## LONG RANGE WIRELESS 11N OUTDOOR AP/CB

IEEE802.11b/g/n    2T+2R    300Mbps    High Performance

- Power Adapter 24V / 0.6A

RF Specification				
Frequency Band	802.11b/g/n			
Data rate	300 Mbps			
Radio Frequency Band (The Max. Power may be different depending on local regulations)	Channel	Data Rate	Tx Avg. Power (±2dBm)	Rx Sensitivity (±2dBm)
	802.11b(2.412 ~ 2.472GHz)	1Mbps	26	-95
		2Mbps	26	-95
		5.5Mbps	26	-93
		11Mbps	26	-93
	802.11g(2.412 ~ 2.472GHz)	6Mbps	26	-95
		9Mbps	26	-93
		12Mbps	26	-93
		18Mbps	26	-93
		24Mbps	26	-92
		36Mbps	25	-80
		48Mbps	24	-77
	802.11n(2.412 ~ 2.472GHz)	MCS0 / MCS8	26	-95
		MCS1 / MCS9	26	-93
		MCS2 / MCS10	26	-92
		MCS3 / MCS11	26	-90
MCS4 / MCS12		25	-86	
MCS5 / MCS13		24	-83	
MCS6 / MCS14		23	-76	
MCS7 / MCS15	22	-73		
Antenna	2 x External SMA Connector			

Environment & Mechanical	
Temperature Range	Operating -20°C~70°C Storage -30°C to 80°C
Humidity (non-condensing)	0%~90% typical
Dimensions	186mm (L) x 100mm (W) x 29mm (H)

**ENS202EXT**  
**LONG RANGE WIRELESS 11N OUTDOOR AP/CB**

IEEE802.11b/g/n    2T+2R    300Mbps    High Performance

<b>Weight</b>	300g
---------------	------